

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : E21B 47/10, 36/04, 47/06, 47/12		A1	(11) International Publication Number: WO 00/11317
		(43) International Publication Date: 2 March 2000 (02.03.00)	
(21) International Application Number: PCT/US99/19781		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 25 August 1999 (25.08.99)			
(30) Priority Data: 60/097,783 25 August 1998 (25.08.98) US			
(71) Applicant (for all designated States except US): BAKER HUGHES INCORPORATED [US/US]; Suite 1200, 3900 Essex Lane, Houston, TX 77027 (US).			
(72) Inventors; and (75) Inventors/Applicants (for US only): WILLIAMS, Glynn [GB/GB]; Roman House, Northway, Walworth Industrial Estate, Andover, Hampshire SP10 5QD (GB). NEUROTH, David, H. [US/US]; 18305 South 4185 Road, Claremore, OK 74017 (US). DALRYMPLE, Larry, Verl [US/US]; 5650 S.E. Roden Road, Claremore, OK 74017 (US).			
(74) Agents: ROWOLD, Carl, A. et al.; Baker Hughes Incorporated, Suite 1200, 3900 Essex Lane, Houston, TX 77027 (US).			

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD OF USING A HEATER WITH A FIBER OPTIC STRING IN A WELLBORE

(57) Abstract

The present invention provides a heater cable (10) that may be deployed in a wellbore to elevate the temperature of the wellbore above the temperature of the surrounding fluid and the formation. One or more fiber optic strings are included in or are carried by the heater cable. The heater cable carrying the fiber optics is placed along the desired length of the wellbore. At least one fiber optic string measures temperature of the heater cable at a plurality of spaced apart locations. Another string may be utilized to determine the temperature of the wellbore. In one aspect of this invention, the heater cable is heated above the temperature of the wellbore. The fluid flowing from the formation to the wellbore lowers the temperature of the cable at the inflow locations. The fiber optic string provides measurements of the temperature along the heater cable. The fluid flow is determined from the temperature profile of the heater cable provided by the fiber optic sensors.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD OF USING A HEATER WITH A FIBER OPTIC STRING IN A WELLBORE

1. Field of the Invention

This invention relates to utilizing fiber optic sensor strings with heater cables for use in oil wells and more particularly for determining the flow of formation fluid into the wellbore and to control the operation of the heater cables for optimum operations.

2. Background of the Art

Heater cables are often used in wellbores to increase the temperature of the fluid in the wellbore to prevent the formation of paraffins and to prevent the oil from flocculating. Such phenomena cause at least some of the oil to become highly viscous, and often plugs the perforations. Such fluids can clog the electrical submersible pumps. Heater cables are also used to heat the formation surrounding the wellbores which contain heavy (highly viscous) oil to reduce the viscosity of such oil.

The heater cable usually is a resistance heating element. High current supplied from the surface can heat the cable to a temperature substantially higher than the formation temperature. In ESP applications, a heater current

may be deployed below the ESP. In other production wells, heater cable may be installed along any desired portion or segment of the wells. It is desirable to determine the fluid flow from various production zones along a wellbore and to monitor and control the temperature of the heater cable so as to heat the wellbore only as required for optimum recovery and to reduce power consumption.

U.S. Patent 4,435,978 discloses a hot wire anemometer in which heat is supplied at a constant rate to a sensor element with fluid flowing past the element. The drop in temperature of the sensor element is used to give a measurement of the fluid flow. This method accurately measures the flow under a variety of flow conditions.

U.S. Patent Ser. No. 5,551,287 discloses a wireline device in which a hot film anemometer deployed on sensor pads measures the temperature of fluid entering the borehole. The fluid flowing past the sensor element produces a change in resistance that is used in a bridge circuit to give a measurement of temperature. This temperature measurement, when combined with a measurement of local ambient temperature, gives an indication of the rate of fluid flow into the borehole. U.S. Patent 4,621,929 discloses a fiber optic thermal anemometer using a sensor element with temperature sensitive optical properties.

The present invention is an apparatus and method for monitoring the fluid flow from a producing well with a plurality of producing intervals. A cable that includes a number of fiber optic thermal anemometer sensors is deployed in the producing well with the sensors in the vicinity of the perforations in the casing or inlets from which fluid from the reservoirs enters the production casing. The present invention also provides temperature distribution along the heater cable length which information is utilized to control the operation of the heater cable.

SUMMARY OF THE INVENTION

The present invention provides a heater cable that may be deployed in a wellbore to elevate the temperature of the wellbore above the temperature of the surrounding fluid and the formation. One or more fiber optic strings are included in or are carried by the heater cable. The heater cable carrying the fiber optics is placed along the desired length of the wellbore. At least one fiber optic string measures temperature of the heater cable at a plurality of spaced apart locations. Another string may be utilized to determine the temperature of the wellbore. In one aspect of this invention, the heater cable is heated above the temperature of the wellbore. The fluid flowing from the formation to the wellbore lowers the temperature of the cable at the inflow locations. The fiber optic string provides measurements of the temperature along the heater cable. The fluid flow is determined from the temperature profile of the heater cable

provided by the fiber optic sensors. In another aspect of this invention, the temperature distribution along the heater cable is used to control the operation of the heater cable to maintain the elevated temperature within desired limits.

The heater cable may be selected turned on and turned off to provide only the desired amount of heat. This may be accomplished by selectively turning on and turning off the heater cable or by increasing and decreasing the electric power supplied as a function of the downhole measured temperatures.

BRIEF DESCRIPTION OF THE DRAWINGS

For detailed understanding of the present invention, references should be made to the following detailed description of the preferred embodiment, taken in conjunction with the accompanying drawings, in which like elements have been given like numerals, wherein:

FIG. 1A shows a portion of a heater cable carrying fiber optic strings according to the present invention.

FIG. 1B shows the cable of **FIG. 1A** deployed in a producing borehole that penetrates a number of reservoirs.

FIG. 2 shows a heater cable deployed in a wellbore being controlled by

a control unit as a function of the temperature measurements provided by the fiber optic sensors in the cable.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1A shows a portion of a cable **10** according to one embodiment of the present invention. It includes a heater cable **20** that carries electrical current and is used as a source of heat by means of uniformly dispersed resistive elements within a portion of the cable (not shown). The cable also includes a pair of fibers **30a**, **30b** for carrying optical signals down the borehole and back up the borehole and for measuring temperature at spaced locations along the fibers.

FIG. 1B shows the cable **10** deployed in a producing borehole **50** that penetrates a number of reservoirs. For illustrative purposes, three producing intervals **40a**, **40b** and **40c** are shown. For illustrative purposes only, each of the three producing intervals is assumed to have a uniform temperature of T_0 .

Further, each of the three producing intervals has a different rate of flow, denoted by Q_1 , Q_2 , Q_3 , of reservoir fluid into the producing well **50**. A plurality of fiber optic sensors, **60a**, **60b**, **60c**..... **60n** in the cable **10** make continuous measurements of temperature at the respective locations. To determine the flow rate from the various zones Q_1 - Q_3 , a control unit **60**

provides power to the heater cable **20**, to cause it to heat the wellbore **50** to a temperature T_1 that is significantly higher than T_o . The fluid flowing from the zones **40a-40e**, which causes the temperature of the heater cable **20** to drop at the flow locations. Under these conditions, the greater the flow rate of fluid Q_i past a sensor, the greater the temperature of the sensor will drop from T_i towards T_o . Measurements of temperature of the sensor are used as an indication of the flow of the formation fluid into the wellbore **50**.

The control unit **60** receives the signals from the fiber optic strings **30a-30b** and can be programmed to calculate the fluid flow from each zone. A log such as shown by the resultant log **70** may be continuously displayed and recorded by the control unit **60**. The log **70** shows a temperature profile along the well **50**. An example of the affect on the temperature curve **80** of the flow from zones **Q1-Q3** respectively is shown at locations **80a-80c**.

Fig. 2 shows a heater cable **100** made according to the present invention, deployed or placed in a wellbore **110** having a casing **112**. The cable **100** includes one or more fiber optic string **120** adapted to measure temperature at spaced apart locations T_1-T_n along a segment or portion of the cable **100** shown by the dotted line. The heater cable **100** is adapted to heat any desired segment of the cable. For convenience, the heater cable herein is assumed to carry heating elements that heat the segment from T_1-T_n . A power unit **130**

supplies power to the heating element 111. A control unit 140 controls the power unit 130, and an optical energy and data unit 142.

The heater element 111 is heated to a predetermined temperature to enhance production flow to the surface. The fiber optic string continuously provides the temperature profile along the wellbore via sensor T1-Tn. If the temperature of the cable 100 in the wellbore is outside a predetermined norm, the control unit 140 adjusts the power to the cable 100 until the heater cable temperature provided by T1-Tn falls back in the desired limits. The control unit may be programmed to selectively turn on and turn off the heater cable to optimize the power consumption and to enhance the operating life of the heater cable.

The heater cable 100 may be deployed below an electrical submersible pump (ESP) when used as shown in Fig. 2 and also above the ESP. The temperature distribution T1-Tn along the heater cable is also useful in predicting heater cable 100 failures. It provides indication of hot spots in the heater cable and the efficiency of the cable corresponding to the input power.

Since the current supplied to the heater element 111 is the same, the heat generated by a uniform heater element will be uniform. The temperature distribution T1-Tn can thus provide indication of the quality of the heater cable's

110 performance.

While the foregoing disclosure is directed to the preferred embodiments of the invention, various modifications will be apparent to those skilled in the art. It is intended that all variations within the scope and spirit of the appended claims be embraced by the foregoing disclosure.

WHAT IS CLAIMED IS:

1. A method of determining flow of fluid from a formation into a wellbore, comprising:

providing a heater cable with a fiber optic string adapted to measure temperature at selected spaced apart locations along said heater cable;

placing said heater cable along a segment of said wellbore that is receiving fluid from adjacent formation;

heating the heater cable to a temperature above the temperature of the wellbore at said selected segment;

measuring a temperature profile along said heater cable by said fiber optic string; and

determining from said temperature profile flow of fluid from said formation into the wellbore.

2. The method of Claim 1 further comprising:

providing a control unit at the surface for receiving temperature measurements from said fiber optic string.

3. The method of Claim 2 further comprising:

providing a temperature log of said wellbore from said temperature measurements.

4. A method of controlling the operation of a heater cable deployed in a wellbore, said heater cable heating a segment of said wellbore to enhance production of fluids through the wellbore, said method comprising:

providing a heater cable with a fiber optic string adapted to measure temperatures at spaced apart locations along said heater cable;


deploying said heater cable at a selected location in said wellbore;

providing power to said heater cable to heat the wellbore to a first temperature;

measuring temperature at selected locations by the fiber optic string; and

adjusting the power to the heater cable as a function of the temperature measurements.

5. The method of claim 4 further comprising providing a control unit at the surface, said control unit controlling the supply of power to the heater cable as a function of the temperature measurements.






FIG 2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/19781

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B47/10 E21B36/04 E21B47/06 E21B47/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	WO 99 45235 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.) 10 September 1999 (1999-09-10) page 5, line 18 -page 6, line 6 page 6, line 28 - line 29 claims 3,4 page 4, line 14 - line 18 ---	1-5
A	US 5 582 064 A (KLUTH) 10 December 1996 (1996-12-10) claims 8,9,16 ---	1,4
A	WO 96 09461 A (SENSOR DYNAMICS LIMITED) 28 March 1996 (1996-03-28) abstract page 7, line 20 -page 8, line 8 --- -/--	1,4

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

5 January 2000

Date of mailing of the international search report

17/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5816 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Sogno, M

INTERNATIONAL SEARCH REPORT

Inter. Appl. No.
PCT/US 99/19781

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 435 978 A (GLATZ) 13 March 1984 (1984-03-13) cited in the application column 1, line 63 - line 68 ---	1,4
A	US 5 551 287 A (MAUTE) 3 September 1996 (1996-09-03) cited in the application column 3, line 8 - line 18 ---	1,4
A	US 4 296 318 A (MEZZETTI) 20 October 1981 (1981-10-20) abstract ---	1,4
A	US 4 832 121 A (ANDERSON) 23 May 1989 (1989-05-23) abstract ---	1,4
A	US 4 621 929 A (PHILLIPS) 11 November 1986 (1986-11-11) cited in the application abstract -----	1,4

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 99/19781

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9945235 A	10-09-1999	NONE	
US 5582064 A	10-12-1996	AT 145058 T AU 4268593 A BR 9306311 A CA 2118229 A DE 69305845 D DE 69305845 T DK 638163 T EP 0638163 A WO 9322645 A GB 2280752 A,B NO 944144 A	15-11-1996 29-11-1993 30-06-1998 11-11-1993 12-12-1996 12-06-1997 14-04-1997 15-02-1995 11-11-1993 08-02-1995 31-10-1994
WO 9609461 A	28-03-1996	AU 3527195 A GB 2307706 A,B US 5804713 A	09-04-1996 04-06-1997 08-09-1998
US 4435978 A	13-03-1984	NONE	
US 5551287 A	03-09-1996	CA 2209918 A EP 0807202 A WO 9623957 A	08-08-1996 19-11-1997 08-08-1996
US 4296318 A	20-10-1981	IT 1159115 B DE 2938312 A FR 2436976 A GB 2036302 A,B	25-02-1987 10-04-1980 18-04-1980 25-06-1980
US 4832121 A	23-05-1989	CA 1296618 A WO 8902972 A	03-03-1992 06-04-1989
US 4621929 A	11-11-1986	AT 44614 T CA 1230240 A EP 0144630 A JP 60098345 A	15-07-1989 15-12-1987 19-06-1985 01-06-1985

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)